

# Strobe light SOX

## General information

Compact xenon strobe light with updated technology, for use in security systems and buildings.

Wide operating voltage range, low consumption, automatic synchronisation.



## Technical details

Base	ABS
Lens	PC
Lens colours	red, amber, green, blue, clear
Temperature range	VDC: -20°C up to +70 °C VAC: -20°C up to +55 °C
Operation	continuous
Flash frequency	60 flashes per minute
Dimensions	Ø 93mm VDC: height 64mm VAC: height 93mm
Weight	VDC: 0,15kg VAC: 0,18kg

## Ordering data

Item Number	Nominal tension	Output	Current consumption	Degree of protection
SOX10.060.2*	9-60VDC	10cd	185mA at 12VDC	IP54 (IP65 with deep base)
SOX10.230.7*	110-230VAC	10cd	40mA at 230VAC	IP65
(consists of SOX10.060.* and powered base B-SO.230.7*)				
SOX15.060.2*	9-60VDC	15cd	510mA at 12VDC	IP54 (IP65 with deep base)
(the powered base can not be used with SOX15.060.2*)				

**\*lens colours** 1 = red , 2 = amber, 4 = green, 5 = blue, 7 = clear

## Options

B-SO.230.7*	Base110-230VAC
A-SO.000.0*	Deep base, Knockouts being opposite
U-SO.000.0*	U-shape base, 2 Knockouts being on the same side

**Case colour** 1 = red, 6 = white

Modification of technical details without prior notice

